

Glitel GW-210

VoIP Gateway



Specification

Compat VoIP gateway Glitel GW-210 allows to use analog phone for voice communication in IP network. Simple and functional design of Glitel GW-210 hides one WAN connector, one LAN connector and one FXS connector for connecting the analog phone. Easy installation, automatic configuration and easy use are the advantages of this device. Glitel GW-210 is suitable for use in homes, small and medium businesses.

Functions and features

- 1x WAN, 1x LAN and 1x FXS connector
- Stable performance
- Compact dimensions
- Possibility of connection one analog phone
- Possibility of connection PC or other LAN device
- Implemented router function
- Automatic configuration, possibility of manual configuration using WEB menu
- Telnet / http Server / DNS Client
- Calling functions waiting for call, call forwarding, caller ID

Parameters

- Interface: 1x WAN, 1x LAN, 1x FXS
- Support: SIP V1 (RFC2543) V2 (RFC3261)
IP/ TCP/ UDP/ RTP/ RTCP/ ICMP/ ARP/ RARP/ SNTP
TFTP Client / DHCP Client / PPPoE Client / Static IP
Telnet, HTTP Server / DNS Client
Codec G.711, G.723, G.726, G.729A, G.729B
QoS, ToS field, NAT
In Band DTMF
Out Band DTMF
SIP info
3 SIP accounts
Outbounng Proxy
HTTP 1.1 basic/ digest autentification for WEB configuration
- Functions: VAD (Voice Activity Detector)
CNG (Comfort Noise Generator)
LEC (Line Echo Canceller)
Adaptive Jitter Buffer
WEB menu
TFTP, HTTP Configuration
- Dimensions: 150 mm x 112 mm x 30 mm
- Weight: 190g

Package

- 1x VoIP gateway Glitel GW-210
- 1x Power adapter
- 1x RJ11 Telephone line cable
- 1x RJ45 Ethernet cable
- 1x User manual